


OLYMPUS[®]

PT-EP06



Instruction Manual

EN



- Thank you for buying the Underwater Case PT-EP06 (hereinafter Case).
- Please read this instruction manual carefully and use the product safely and correctly. Please keep this instruction manual for reference after reading it.
- Wrong usage may cause damage to the camera inside the Case due to water leakage, and repair may not be possible.
- Before use, perform an advance check as described in this manual.

Introduction

- Unauthorized copying of this manual in part or in full, except for private use, is prohibited. Unauthorized reproduction is strictly prohibited.
- OLYMPUS IMAGING CORP. shall not be responsible in any way for lost profits or any claims by third parties in case of any damage occurring from improper use of this product.

Please read the following items before use

- This Case is a precision device designed for use at a water depth within 45 m. Please handle it with sufficient care.
- Please use the Case correctly after sufficient understanding of the contents of this manual in regard to handling of the Case, checks before use, maintenance, and storage after use.
- OLYMPUS IMAGING CORP. shall not be responsible for accidents involving immersion of a digital camera in water. In addition, expenses incurred for damage of internal materials or loss of recorded contents due to water entering the camera will not be compensated.
- OLYMPUS IMAGING CORP. shall not pay any compensation for accidents (injuries or material damage) at the time of use.

For safe use

This instruction manual uses various pictographs for correct use of the product and to prevent danger to the user and other person, as well as property damage. These pictographs and their meanings are shown below.

 WARNING	This shows the content regarding assumption of possibility of human death or severe injury in case of handling with disregard of this indication.
 CAUTION	This shows the contents regarding assumption of possibility of injury or damage to property in case of handling with disregard of this indication.

WARNING

- ① Keep this product out of the reach of babies, infants, and children. There is the possibility of occurrence of the following types of accidents.
 - Injury by dropping onto the body from heights.
 - Injury from parts of the body getting caught in parts which open and close.
 - Swallowing of small parts, O-ring, silicone grease and silica gel. Please consult a physician immediately if any parts have been swallowed.
- ② Do not store digital camera with batteries inserted in this product.
Storage with a battery inserted may lead to leakage of the battery liquid and fire hazard.
- ③ If leakage of water should occur with a camera installed in this product, quickly remove the battery from the camera. There is the possibility of ignition and explosion from generation of hydrogen gas.
- ④ This product is made of resin. There is the possibility that injuries may be caused when it becomes broken due to strong impact with a rock or other hard objects. Please handle it with sufficient care.

CAUTION

- ① Do not disassemble or modify this product. This may cause water leakage or defect. In case of the loss of image data caused by disassembly, repair or modification etc. by any party other than those appointed by OLYMPUS IMAGING CORP., we shall bear no responsibility for damage.
- ② Use or storage of the product at the following locations may cause defective operation, defects, damage, fire, internal fogging, or water leakage. This should be avoided.
 - Locations reaching high temperatures such as those under direct sunlight, in an automobile, etc.
 - Locations close to fire
 - A water depth in excess of 45 m
 - Locations subject to vibrations
 - Locations with high temperature and humidity or with extreme temperature changes
 - Locations with volatile substances
- ③ Opening and closing at locations with much sand, dust, or dirt may impair the waterproof characteristic and cause water leakage. This should be avoided.
- ④ This product is not a case to soften impacts to the camera inside the product. When this product with a digital camera inside is subjected to impacts or heavy objects are placed onto it, the digital camera may be damaged. Please handle it with sufficient care.
- ⑤ Do not use the following chemicals for cleaning, corrosion prevention, prevention of fogging, repair or other purposes. When these are used for the Case directly or indirectly (with the chemicals in vaporized state), they may cause cracking under high pressure or other problems.

Chemicals which cannot be used	Explanation
Volatile organic solvents, chemical detergents	Do not clean the Case with alcohol, gasoline, thinner or other volatile organic solvents or with chemical detergents etc. Pure water or lukewarm water is sufficient for cleaning.
Anticorrosion agent	Do not use anticorrosion agents. Pure water is sufficient when washing the metal parts as stainless steel and brass are used.
Commercial defogging agents	Do not use commercial defogging agents. Always use the specified desiccant silica gel.
Grease other than specified silicone grease	Use only the specified silicone grease for the O-ring, as otherwise the O-ring surface may deteriorate and water leakage may occur.
Adhesive	Do not use adhesive for repairs or other purposes. When repair is required, please contact a dealer or a service station of OLYMPUS IMAGING CORP.



- ⑥ Jumping into the water with the Case in your hand, throwing the Case from a boat or ship into the water, and other rough handling may cause water leakage. Please handle with sufficient care, when handing it over from hand to hand etc.
- ⑦ If the Case interior or the camera should become wet because of water leakage, etc., immediately wipe off all moisture and contact your local service station or dealer.
- ⑧ Be careful not to apply excessive force to the zoom dial, accessory mount or tripod seat.
- ⑨ Please remove the O-ring when traveling by air. Otherwise air pressure may make it impossible to open the Case.
- ⑩ For safe use of the digital camera in this product, please read the "Instruction Manual" for the digital camera carefully.
- ⑪ When sealing this product, take sufficient care that no foreign matter gets caught at the O-ring and the contact surface. It is caused for water leakage.
- ⑫ You cannot take pictures by using only the camera's built-in flash when the digital camera is in the Case.
- ⑬ The lens port cannot be removed.

Contents

Introduction	1
Please read the following items before use	1
For safe use	1
1.Preparations.....	5
Check the contents of the package.....	5
Names of the parts.....	6
Using the accessories	7
Installing and removing of the LCD hood.....	7
Mounting and removing the body cap.....	7
2.Advance check of the Case.....	8
Advance check before use.....	8
3.Loading the digital camera.....	9
Check the digital camera.....	9
Open the Case	10
Attach the flash to the camera and raise the light emitting part	10
Load the digital camera	11
Make sure the camera is loaded properly	11
Seal the Case.....	12
Check the operation of the loaded camera	12
Water leakage test	13
4.Connecting the underwater flash.....	14
Connecting the underwater optical fiber cable	14
5.Taking pictures under water	15
Select the shooting modes.....	15
Underwater shooting modes	15
6.Handling after shooting	16
Wipe off any waterdrop	16
Unload the digital camera	16
Wash the Case with pure water	16
Dry the Case	17
7.Maintaining the waterproof function.....	18
Remove the O-ring.....	18
Remove any sand, dirt, etc.	18
Install the O-ring.....	18
Applying grease to the O-ring	19
Replace consumable products.....	19
8.Appendix	20
Specifications	20
Supplied accessories for PT-EP06	20
Optional accessories.....	20

1. Preparations

Check the contents of the package


Check that all accessories are in the box.
Contact your dealer if accessories are missing or damaged.

- Case body
(Check that the O-ring is installed.)
 - LCD hood (on the body)
 - Silica gel (1g)
 - Body cap
 - O-ring remover
 - Silicone grease
 - Hand strap
 - Optical fiber cable insertion slot cap (2)
 - Flash window cover
 - Instruction manual (this manual)
-

⚠ CAUTION:

- After purchase, be sure to do maintenance even in brand-new condition. Neglecting the maintenance may become the cause of water leakage.
For how to maintenance the case, refer to P.18.

Names of the parts



- | | | |
|---|--|---|
| <ul style="list-style-type: none"> ① Open/close dial ② Slide lock *③ Shutter lever *④ ON/OFF button ⑤ Accessory mount ⑥ Light ON/OFF button (for PT-EP05L/06L)
*1 Not used with PT-EP06. ⑦ Optical fiber cable insertion slots | <ul style="list-style-type: none"> ⑧ Zoom dial ⑨ ● (REC) button *⑩ INFO (Info display) button *⑪ (Exposure correction) button/Cross-cursor button ⑫ button/Q button/Cross-cursor button *⑬ OK button *⑭ button/Cross-cursor button | <ul style="list-style-type: none"> *⑮ MENU button *⑯ (Play) button ⑰ button/ button/Cross-cursor button ⑱ LCD monitor window ⑲ LCD hood ⑳ O-ring ㉑ LCD inner hood ㉒ Tripod seat |
|---|--|---|

Note:

Case operation parts marked by * corresponds to the operation parts of the digital camera. When the operation parts of the Case are operated, the corresponding functions of the digital camera will operate. For details of the functions, refer to the instruction manual for the digital camera.

Using the accessories


Installing and removing of the LCD hood

Installation

Fit the LCD hood as shown in the figure into the rails above and below the LCD monitor window one after the other.


Removal

Remove the LCD hood from the rails above and below the LCD monitor window one after the other by widening the LCD hood.



Mounting and removing the body cap

Install to fit the concave and convex parts of the body cap and lens port. Be sure to remove the body cap before shooting.



2. Advance check of the Case

Advance check before use

This Case has been the subject of thorough quality control for the parts during the manufacturing process and thorough function inspections during the assembly. In addition, a water pressure test is performed with a water pressure tester for all products to confirm that the performance conforms to the specifications.

However, depending on the carrying, storage conditions and the maintenance status, etc., the waterproof function may be damaged.

Before using, always perform the following advance checks.

Advance check

- ① Before loading the digital camera in the Case, immerse the empty Case to confirm that there is no water leakage. When it is difficult, water leakage can be checked by referring "Water leakage test" (P. 13).
- ② Main causes of water leakage are as follows.
 - Forgetting to install the O-ring
 - Part of an O-ring or an entire O-ring is outside the specified groove.
 - O-ring damage, cracks, deterioration or deformation
 - Sand, fibers, hair or other foreign matter sticking to the O-ring, the O-ring groove or the O-ring contact surface.
 - Damage to an O-ring groove or O-ring contact surface.
 - Attached strap or silica gel getting caught when closing the Case.

Perform the test after the above causes have been eliminated.

 **CAUTION:**

If the advance test should show water leakage with normal handling, stop using the Case and contact your dealer or an Olympus service station.

3. Loading the digital camera

Check the digital camera

Check the digital camera before loading it in the Case.

1. Battery confirmation

It is impossible to change the batteries when using the Case. Make sure that you have sufficient remaining battery capacity before use.

2. Check the remaining number of pictures


Check that the image storage medium has enough room for the number of pictures you want to take.

3. Remove the strap, lens cap and filter from the digital camera.

If the digital camera is loaded without removing the strap, lens cap and the Case cannot be sealed properly and water leakage may be caused.

4. Attach the zoom gear (optional) and the antireflective ring (optional).

Example of 14-42mm II lens




For details, refer to the instruction manual of the zoom gear and the antireflective ring.

	Zoom gear	Antireflective ring
M.ZUIKO DIGITAL ED 14-42mm	PPZR-EP01	POSR-EP01
M.ZUIKO DIGITAL 14-42mm II/IIR	PPZR-EP02	POSR-EP03
M.ZUIKO DIGITAL ED 9-18mm	PPZR-EP02	POSR-EP02

Open the Case

- ① Slide and hold the slide lock towards the arrow direction (①) and turn the open/close dial clockwise (②).
- ② Open the rear lid of the Case gently.




⚠ CAUTION:

Do not apply too much force while turning the open/close dial. Doing so may damage the dial.


Attach the flash to the camera and raise the light emitting part

Attach the flash supplied with the camera.
Make sure to raise the light emitting part.



Load the digital camera

- ① Confirm that the digital camera is OFF.
- ② Gently load the digital camera into the Case.
- ③ Insert a silica gel bag (1g) between the bottom of the digital camera and the Case. The silica gel bag provided for prevention of fogging.



⚠ CAUTION:

- If the silica gel bag is caught when the Case is sealed, water leakage will occur.
- Once silica gel has been used, the moisture absorption performance will be impaired. Always replace the silica gel when the Case is opened and closed.
- Clean the surface of the dials of the Case and the camera. The dials may slip if there is grease or foreign matter on them.


Make sure the camera is loaded properly

Check the following points before sealing the Case.

- Is the digital camera loaded properly?
- Is silica gel inserted all the way at the specified location?
- Is the O-ring attached properly to the opening on the Case?
- Is there any dirt or foreign matter on the O-ring or the O-ring contact surface on the front lid?
- Is the waterproof function maintenance performed? (For details of the maintenance, refer to "Maintaining the waterproof function" (P. 18) of this manual.)

Seal the Case

- ① Close the Case gently while aligning the mounting projection of the rear lid and groove of the open/close dial.
- ② Turn the open/close dial counter clockwise.
 - The Case is sealed.



⚠ CAUTION:

- If the open/close dial is not fully turned, the Case will not be sealed. This will cause water leakage.
- Close the rear lid of the Case so that the lens cap or LCD hood strap is not caught. If it is caught, water leakage may be caused.

Check the operation of the loaded camera


After sealing the Case, check that the camera operations normally.

- Push the ON/OFF button on the Case and confirm that the camera turns ON/OFF.
- Turn the mode dial knob on the Case and confirm that the camera mode switches properly.
- Press the shutter lever on the Case and confirm that the camera shutter releases.
- Operate the zoom dial on the Case and confirm that the camera's lens is controlled.
- Operate other control buttons on the Case and confirm that the camera functions properly as intended.

Water leakage test

The final test after loading the camera is explained below. Always perform this test. It can be performed easily in a water tank or a bathtub. The required time is about five minutes. Confirm the operation of the different buttons.

- At first, immerse the Case for only three seconds and check that no water drop etc. to inside of the Case.
- Next, immerse the Case for 30 seconds and check that no water drop etc. to inside of the Case.
- Then, immerse the Case for three minutes, operate all buttons and levers, and check the following:
 - check that no water has accumulated inside of the Case.
 - check that the Case is not fogged.
 - check that no water has entered inside of the Case.
- If inside of the Case is fogged or there is a water drop, do the maintenance of the O-ring and perform the water leakage test again.




4. Connecting the underwater flash

Connecting the underwater optical fiber cable


To connect the UFL-2 underwater flash (optional) to the Case using an underwater optical fiber cable (optional: PTCB-E02), follow the procedures below.

Connecting the underwater optical fiber cable

- ① Put the underwater optical fiber cable plug into the optical fiber cable insertion slot. Insert firmly until it stops next to the flash window cover.



- ② Put the cap to the optical fiber cable insertion slot when not in use.



Setting of the digital camera

Set the RC mode of the camera to ON so that the camera's built-in flash is activated.

In case of UFL-2, turn the RC mode to ON.
For details, refer to the instruction manual of UFL-2.

In case of UFL-1, plug the optical fiber cable in the same way.
Turn the RC mode of the camera to OFF.

5. Taking pictures under water

Select the shooting modes

Assign the underwater mode to a ●(REC) button or Cross-cursor button ▼ to easily switch to that mode. Select [📷/📷] in [Button Function] in [B] of [📷] in [MENU], then press the OK button.

* [📷] menu display of [1] in [MENU] must be set to ON.

Note:

- Press the ●(REC) button or Cross-cursor button ▼ to switch between Underwater Wide-Angle and Underwater Macro modes.
- Turn the mode dial knob or hold down the ●(REC) button or Cross-cursor button ▼ to exit the underwater mode. Press the ●(REC) button or Cross-cursor button ▼ again to return to the underwater mode.
- However, in SCN, iAUTO and movie modes, pressing the Fn button will not set the camera in underwater mode.

For details, refer to the instruction manual of the digital camera.

Underwater shooting modes

■ 📷 Underwater Wide-Angle

Suitable for shooting a scene that extends across a wide range such as a school of fish swimming through the water. Background blues are vividly reproduced.

■ 📷 Underwater Macro

Suitable for close-up shooting of small fish and other underwater creatures. Natural colors of the underwater are accurately reproduced.

6. Handling after shooting

Wipe off any waterdrop

After underwater shooting, remove any water drop from the case. Use pressurized air or a soft, lint-free cloth to carefully wipe away any moisture from the hinge between the front and rear lids, the shutter lever and the open/close dial.

 CAUTION:

Water left between the front and rear lids can get inside the Case once it is opened. Please dry these areas carefully.

Unload the digital camera

Open the Case carefully and take the digital camera out.

 CAUTION:

- When opening the Case, make sure no water from outside (e.g. drops from your hair or the diving suit) gets inside the Case and/or on the camera.
- Before opening the case, ensure that your hands or gloves are completely clean (free of sand, loose fibers, etc.).
- Never open the Case in areas where water could splash or spray or where sand or dust could be blown in the air. When this cannot be avoided, for example if the battery or memory card needs to be changed, the Case and camera should be protected from the wind or spray with a plastic sheet or similar object.
- Never touch the digital camera and/or battery when your hands are wet with sea water.

Wash the Case with pure water

After use, seal the Case again after taking out the camera and wash it sufficiently in pure water as soon as possible.

After use in sea water, it is effective to immerse it for a fixed time (30 minutes to 1 hour) in pure water to remove any salt.

 CAUTION:

- Water leakage may occur when a high water pressure is applied partially. Before washing the Case with water, remove the digital camera from it.
- Operate the shutter lever and each buttons of this product in pure water to remove salt adhering to the shaft. Do not disassemble for cleaning.
- Letting salt dry on the Case may impair the function. Always wash off any salt after use.



Dry the Case

After washing with pure water, use a lint-free soft cloth without any salt on it to wipe off any water drop and dry the Case completely at a well ventilated location in the shade.

 **CAUTION:**

Do not use hot air from a hair drier or the like for drying and do not expose the Case to direct sunlight, as this may accelerate deterioration and deformation of the Case and deterioration of the O-ring, leading to leakage of water.

When wiping the Case, take care not to cause scratches.

7. Maintaining the waterproof function

The O-ring is a consumable product. Before each use, perform proper maintenance. Always be sure to perform the O-ring maintenance operation as described below. Neglecting this maintenance may become the cause of water leakage.

Perform at the location without sand or dust, after washing and drying your hands.

Remove the O-ring

Open the Case and remove the O-ring.

Procedure

- ① Insert the O-ring remover into the gap between the O-ring and O-ring groove wall.
- ② Bring the tip of the inserted O-ring remover below the O-ring. (Be careful not to damage the groove with the tip of the O-ring remover.)
- ③ Lift the O-ring, pinch it with your fingertips and pull it out of the Case.

Remove any sand, dirt, etc.

After visually checking that dirt has been removed from the O-ring, check for attached sand and other foreign matter, as well as for damage and cracks by squeezing the entire circumference of the O-ring lightly with your fingertips.

Remove attached foreign matter from the O-ring groove with a clean cloth or a cotton swab. Also remove any sand or dirt attached to any part of the Case that comes into contact with the O-ring.

⚠ CAUTION:

- When a sharp object is used to remove the O-ring or to clean the inside of the O-ring groove, the Case and the O-ring may be damaged and water leakage may be caused.
- When the O-ring is checked with the fingertips, take care not to stretch the O-ring.
- Never use alcohol, thinner, benzene or similar solvents or chemicals detergents to clean the O-ring. When such chemicals are used, it is likely that the O-ring will be damaged or that its deterioration will be accelerated.

Install the O-ring

Confirm that no foreign matter is attached, apply a thin coat of the accessory grease to the O-ring, and fit the O-ring into the groove. At this time, confirm that the O-ring does not stick out from the groove. When sealing this product, make sure that no hairs, fibers, sand particles or other foreign matter stick not only to the O-ring, but also to the contact surface (front cover). Even a single hair or a single grain of sand may cause water leakage. Please check with special care.

Applying grease to the O-ring

<p>① Apply only Olympus exclusive grease to O-ring.</p>		<p>Make sure that your fingers and the O-ring are free of dirt, and squeeze about 5 mm of grease onto a finger. (5 mm is the most appropriate amount.)</p>
<p>② Spread the grease onto the entire circumference of the O-ring.</p>		<p>Spread the grease onto the entire circumference of the O-ring using 3 fingers. Be careful not to use excessive force as this may stretch the O-ring.</p>
<p>③ Check that the O-ring is free of scratches or unevenness.</p>		<p>After spreading the grease, check visually and by touch that the O-ring is not scratched and that its surface is flat. If it is damaged in any way, replace it with a brand-new O-ring.</p>

⚠ CAUTION:

- Always perform maintenance of the waterproof function even when the Case has been opened every shooting. Neglecting this maintenance may become the cause of water leakage.
- When the Case is not to be used for a long time, remove the O-ring from the groove to prevent deformation of the O-ring, apply a thin coat of silicone grease, and store it in a clean plastic bag or the like.


Examples of foreign matter sticking to the O-ring



Hair



Fibers



Grains of sand

Replace consumable products

- The O-ring is a consumable product. Independent of the number of times the Case is used, it is recommended that the O-ring should be replaced by a new piece at least once a year.
- Deterioration of the O-ring is accelerated by the usage conditions and the storage conditions. Replace the O-ring even before a year has passed if it shows signs of damage, cracking or loss of elasticity.

⚠ CAUTION:

- Use genuine Olympus silicone grease, silica gel and O-ring.
- Do not try to replace the O-ring by yourself.
- We recommend to perform the check periodically.

8. Appendix

Specifications

Underwater case	PT-EP06
Supported camera	E-PM1
Pressure resistance	Depth of down to 45 m (147 feet)
Main materials	Main body: Polycarbonate O-ring: Silicone rubber
Dimensions	Width 175 mm × height 154 mm × depth 165 mm
Weight	Approx. 1,110 g (camera and accessories not included)
Weight under water	Approx. –150 g (in the freshwater)
	(including camera, 14-42mm IIR lens, zoom gear, antireflective ring, batteries and media card)

* We reserve the right to change the external appearance and the specifications without notice.

Supplied accessories for PT-EP06

O-ring: POL-EP03
Silicone grease: PSOLG-2
Silica gel: SILCA-5S
LCD hood: PFUD-EP05
Body cap: PBC-EP01
Flash window cover: PFC-EP05
O-ring remover: PTAC-05

Optional accessories

Silicone grease: PSOLG-3
Underwater optical fiber cable: PTCB-E02
Bracket: PTBK-E01, PTBK-E02
Short arm: PTSA-02/PTSA-03
Underwater flash: UFL-2, UFL-1
Macro lens adapter: PMLA-EP01
Macro lens: PTMC-01
Zoom gear for M.ZUIKO DIGITAL ED 14-42mm F3.5-5.6: PPZR-EP01
Antireflective ring for M.ZUIKO DIGITAL ED 14-42mm F3.5-5.6: POSR-EP01


Zoom gear for M.ZUIKO DIGITAL for 14-42mm II/IIR F3.5-5.6: PPZR-EP02
Antireflective ring for M.ZUIKO DIGITAL for 14-42mm II/IIR F3.5-5.6: POSR-EP03

Zoom gear for M.ZUIKO DIGITAL for 9-18mm F4.0-5.6: PPZR-EP02
Antireflective ring for M.ZUIKO DIGITAL for 9-18mm F4.0-5.6: POSR-EP02

* When use combining PTBK-E01 and the Case, the dedicated washers are necessary in the screw part.
If you have PTBK-E01 to which dedicated washers are not bundled, please contact to customer support center.

Supplied accessories can be purchased. Products of other model types than those describing above cannot be used.





OLYMPUS®

<http://www.olympus.com/>

OLYMPUS IMAGING CORP.

Shinjuku Monolith, 3-1 Nishi-Shinjuku 2-chome, Shinjuku-ku, Tokyo, Japan

OLYMPUS IMAGING AMERICA INC.

3500 Corporate Parkway, P.O. Box 610, Center Valley, PA 18034-0610, U.S.A. Tel. 484-896-5000

Technical Support (USA)

24/7 online automated help: <http://www.olympusamerica.com/support>
Phone customer support: Tel. 1-888-553-4448 (Toll-free)

Our phone customer support is available from 8 am to 10 pm
(Monday to Friday) ET

E-Mail: distec@olympus.com

Olympus software updates can be obtained at: <http://www.olympusamerica.com/digital>

OLYMPUS EUROPA HOLDING GMBH

Premises: Wendenstrasse 14-18, 20097 Hamburg, Germany

Tel: +49 40-23 77 3-0 / Fax: +49 40-23 07 61

Goods delivery: Bredowstrasse 20, 22113 Hamburg, Germany

Letters: Postfach 10 49 08, 20034 Hamburg, Germany

European Technical Customer Support:

Please visit our homepage <http://www.olympus-europa.com>

or call our TOLL FREE NUMBER* : **00800 - 67 10 83 00**

for Austria, Belgium, Denmark, Finland, France, Germany, Italy, Luxemburg, Netherlands,
Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom

* Please note some (mobile) phone services providers do not permit access or request an
additional prefix to +800 numbers.

For all European Countries not listed and in case that you can't get connected
to the above mentioned number, please make use of the following

CHARGED NUMBERS: **+49 180 5 - 67 10 83** or **+49 40 - 237 73 4899**

Our Technical Customer Support is available from 9 am to 6 pm MET (Monday to Friday)